

DESCRIPTION

The Fusi series in typical modular design. Thanks to their powerful LEDs, our swiveling spotlights deliver ideal for indoor lighting. Our spotlights are available in surface-mounted, semi-recessed or track mounted versions, with wide to focused beam angles. They can be used for presentation, in retail situation, or in museums. Very powerful and energy-efficient illumination. The spotlights are great for accentuation, thanks to the precise alignment of the light points. They can be glare-reduced by applying optical accessories such as the Honeycomb Louver. The rotating design allows the light to be turned in the required direction.



QUICKINFO

GENERAL


Finish	Black (RAL 9005)
Material	Die-cast Aluminium
IP	20
Lifespan	L80/50,000h
Warranty	5 years

LED

Optic	Lens
Lumen	1200 / 1500lm
Efficacy	Up to 75lm/W
CRI	3000K
CCT	>95
SDCM	<3
UGR	<13
Beam Angle	36°

ELECTRICAL

Voltage	220-240V
Power	15/20W
Driver (Build-in)	Phase Cut



PURATI PTY LTD


Unit 10, O'Riordan St, Alexandria NSW 2015
 Tel: +61 410343721
 sales@purati.com

CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	65.15	1822	2715
2	130.30	455.4	678.7
3	195.45	202.4	301.6
4	260.60	113.9	169.7
5	325.75	72.87	108.6
Angle: 36.09°			

Fusi 46 Spot Duo Surface
15W 3000K 36°

POLAR DIAGRAM



CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	65.23	2245	3341
2	130.47	561.3	835.2
3	195.70	249.5	371.2
4	260.94	140.3	208.8
5	326.17	89.80	133.6
Angle: 36.13°			

Fusi 46 Spot Duo Surface
20W 3000K 36°

POLAR DIAGRAM

