

## DESCRIPTION

This build-on downlight combines a sleek design with an opal diffuser for even light distribution that perfectly suited for any space, while its simple shape with refined details enriches each interior just by its presence. This luminaire comes in three different colors, two different water resistances and it can be installed in using two mounting options choose from surface mounted and suspended.



## QUICKINFO

## GENERAL


Finish	Black (RAL 9005)
Material	Die-cast Aluminium
IP	20/44
Lifespan	L80/50,000h
Warranty	5 years

## LED

Optic	Opal Diffuser
Lumen	1200 / 850 / 700lm
Efficacy	Up to 100lm/W
CRI	3000K / 4000K
CCT	>90
SDCM	<5
UGR	<23

## ELECTRICAL

Voltage	220-240V
Power	12/8/6W
Driver (Build-in)	Phase cut



## PURATI PTY LTD


Unit 10, O'Riordan St, Alexandria NSW 2015  
Tel: +61 410343721  
sales@purati.com

CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	308.26	60.74	222.80
2	616.52	15.18	55.70
3	924.79	6.749	24.76
4	1233.05	3.796	13.93
5	1541.31	2.430	8.912
Angle: 114.05°			

Pura Build-on 150 6W 3000K

POLAR DIAGRAM




CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	308.65	63.92	234.70
2	617.29	15.98	58.67
3	925.94	7.102	26.08
4	1234.59	3.995	14.67
5	1543.23	2.557	9.387
Angle: 114.11°			

Pura Build-on 150 6W 4000K

POLAR DIAGRAM




CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	310.57	70.73	259.4
2	621.14	17.68	64.85
3	931.71	7.859	28.82
4	1242.29	4.420	16.21
5	1552.86	2.829	10.38
Angle: 114.44°			

Pura Build-on 150 8W 3000K

POLAR DIAGRAM




CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	310.42	74.18	272.2
2	620.85	18.55	68.05
3	931.27	8.242	30.24
4	1241.70	4.636	17.01
5	1552.12	2.967	10.89
Angle: 114.41°			

Pura Build-on 150 8W 4000K

POLAR DIAGRAM




CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	308.88	103.0	379.0
2	617.77	25.74	94.75
3	926.65	11.44	42.11
4	1235.53	6.436	23.69
5	1544.41	4.119	15.16
Angle: 113.21°			

Pura Build-on 150 12W 3000K

POLAR DIAGRAM



CONE DIAGRAM

m	Φ cm	Lux AVG	Lux MAX
1	310.01	107.8	396.0
2	620.02	26.96	99.00
3	930.03	11.98	44.00
4	1240.03	6.739	24.75
5	1550.04	4.313	15.84
Angle: 114.34°			

Pura Build-on 150 12W 4000K

POLAR DIAGRAM

