

## DESCRIPTION

The Slice Series comprises of three classic shapes (Round . Square . Rectangle) that will suit a wide range of projects. The Slice Circle with minimalist design, in rich colors, fine finishing and four sizes. The combination of functionality and performance that can be perfectly suited for both consumer and professional applications. Expertly designed and engineered a build-in driver, quick wiring connection, push lock or turning lock system with quick release buttons which results in making the installation easy.



## QUICKINFO

### GENERAL


|          |                                  |
|----------|----------------------------------|
| Finish   | Black (RAL 9005)                 |
| Material | Die-cast Aluminium/Polycarbonate |
| IP       | 54                               |
| Lifespan | L80/50,000h                      |
| Warranty | 5 years                          |

### LED

|          |                 |
|----------|-----------------|
| Optic    | Opal Diffuser   |
| Lumen    | 3200lm / 2400lm |
| Efficacy | 100lm/W         |
| CRI      | 3000K / 4000K   |
| CCT      | >90             |
| SDCM     | <3              |
| UGR      | <23             |

### ELECTRICAL

|                   |           |
|-------------------|-----------|
| Voltage           | 220-240V  |
| Power             | 32/24W    |
| Driver (Build-in) | Phase cut |



|              |              |        |        |      |      |         |  |
|--------------|--------------|--------|--------|------|------|---------|--|
| Power Switch | Color Switch | CRI>90 | SDCM<3 | IP54 | IK10 | 5 YEARS |  |
|--------------|--------------|--------|--------|------|------|---------|--|

### PURATI PTY LTD


Unit 10, O'Riordan St, Alexandria NSW 2015  
Tel: +61 410343721  
sales@purati.com

CONE DIAGRAM

| m              | Φ<br>cm | Lux<br>AVG | Lux<br>MAX |
|----------------|---------|------------|------------|
| 1              | 336.94  | 169.5      | 679.9      |
| 2              | 673.88  | 42.38      | 170.0      |
| 3              | 1010.82 | 18.83      | 75.55      |
| 4              | 1347.76 | 10.59      | 42.50      |
| 5              | 1684.70 | 6.780      | 27.20      |
| Angle: 118.62° |         |            |            |

Slice Circle 400 24W 3000K

POLAR DIAGRAM




CONE DIAGRAM

| m              | Φ<br>cm | Lux<br>AVG | Lux<br>MAX |
|----------------|---------|------------|------------|
| 1              | 337.48  | 175.7      | 704.3      |
| 2              | 674.95  | 43.93      | 176.1      |
| 3              | 1012.43 | 19.52      | 78.25      |
| 4              | 1349.91 | 10.98      | 44.02      |
| 5              | 1687.39 | 7.028      | 28.17      |
| Angle: 118.70° |         |            |            |

Slice Circle 400 24W 4000K

POLAR DIAGRAM




CONE DIAGRAM

| m              | Φ<br>cm | Lux<br>AVG | Lux<br>MAX |
|----------------|---------|------------|------------|
| 1              | 334.41  | 219.6      | 885.3      |
| 2              | 668.82  | 54.90      | 221.3      |
| 3              | 1003.23 | 24.40      | 98.37      |
| 4              | 1337.63 | 13.72      | 55.33      |
| 5              | 1672.04 | 8.784      | 35.41      |
| Angle: 118.24° |         |            |            |

Slice Circle 400 32W 3000K

POLAR DIAGRAM



CONE DIAGRAM

| m              | Φ<br>cm | Lux<br>AVG | Lux<br>MAX |
|----------------|---------|------------|------------|
| 1              | 336.14  | 224.9      | 903.6      |
| 2              | 672.28  | 56.22      | 225.9      |
| 3              | 1008.41 | 24.99      | 100.4      |
| 4              | 1344.55 | 14.06      | 56.47      |
| 5              | 1680.69 | 8.996      | 36.14      |
| Angle: 118.50° |         |            |            |

Slice Circle 400 32W 4000K

POLAR DIAGRAM

