# **PURATI**

FRTSA - B10315D FRTSA - B10324D FRTSA - B10336D FRTSA - B10360D

#### **DESCRIPTION**

### Thin trim IP54 recessed downlight with minimalistic design and versatile application

The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.




#### QUICKINFO

#### GENERAL

GENERAL	Disab (DAL 0046)
Finish Materiall	Black (RAL 9016) Die-cast Aluminium
IP	Die-cast Aldminidm 54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Optic	15°/24°/36°/60° Reflector
Lumen	1029lm
Efficacy	Up to 100lm/W
CRI	3000K
CCT	>92
SDCM	<3
UGR	<19
ELECTRICAL	
Voltage	220-240V
Power	10W
Driver (Flicker-Free)	Phase cut
ACCESSORIES	
Glass diffuser or honeycomb loa	uver

5 YEARS



PURATI PTY LTD Unit 10, 80 O'Riordan St, Alexandria NSW 2015 Tel: +61 2 8065 8181 sales@purati.com

BEAM 15°/24° / 36° / 60° CRI>92 SDCM<3

## **PURATI**

FRTSA - W10315D FRTSA - W10324D FRTSA - W10336D FRTSA - W10360D

#### **DESCRIPTION**

# Thin trim IP54 recessed downlight with minimalistic design and versatile application

The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.




### QUICKINFO

### GENERAL

D: (A) ::
Die-cast Aluminium
54
L90/50,000h
5 years
15°/24°/36°/60° Reflector
1029lm
Up to 100lm/W
3000K
>92
<3
<19
220-240V
10W
Phase cut

5 YEARS



BEAM 15°/24° / 36° / 60° CRI>92 SDCM<3