Fuoco Round Trimless Fixed Product Coded

PURATI

FRTS - B10315D FRTS - B10324D FRTS - B10336D FRTS - B10360D

DESCRIPTION

Thin trim IP54 recessed downlight with minimalistic design and versatile application


The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.



QUICKINFO

GENERAL

Black (RAL 9016)	Finish
Die-cast Aluminium	Materiall
54	IP
L90/50,000h	Lifespan
5 years	Warranty
	LED
15°/24°/36°/60° Reflector	Optic
1029lm	Lumen
Up to 100lm/W	Efficacy
3000K	CRI
>92	CCT
<3	SDCM
<19	UGR
	ELECTRICAL
220-240V	Voltage
10W	Power
Phase cut	Driver (Flicker-Free)



ACCESSORIES

Glass diffuser or honeycomb louver



PURATI PTY LTD Unit 10, 80 O'Riordan St, Alexandria NSW 2015 Tel: +61 2 8065 8181 sales@purati.com

Fuoco Round Trimless Fixed Product Coded

PURATI

FRTS - W10315D FRTS - W10324D FRTS - W10336D FRTS - W10360D

DESCRIPTION

Thin trim IP54 recessed downlight with minimalistic design and versatile application

The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.




QUICKINFO

GENERAL

Finish Materiall IP	White(RAL9005) Die-cast Aluminium 54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Optic	15°/24°/36°/60° Reflector
Lumen	1029lm
Efficacy	Up to 100lm/W
CRI	3000K
CCT	>92
SDCM	<3
UGR	<19
ELECTRICAL	
Voltage	220-240V
Power	10W
Driver (Flicker-Free)	Phase cut
ACCESSORIES	

5 YEARS



PURATI PTY LTD Unit 10, 80 O'Riordan St, Alexandria NSW 2015 Tel: +61 2 8065 8181 sales@purati.com

Glass diffuser or honeycomb louver

BEAM 15°/24° / 36° / 60° CRI>92 SDCM<3