Fuoco Suqare Trimless Fixed

PURATI

FSTS - B10315D FSTS - B10324D FSTS - B10336D FSTS - B10360D

DESCRIPTION

Thin trim IP54 recessed downlight with minimalistic design and versatile application

The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.




QUICKINFO

ACCESSORIES

GENERAL

Finish Materiall	Black (RAL 9016) Die-cast Aluminium
IP	54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Optic	15°/24°/36°/60° Reflector
Lumen	1029lm
Efficacy	Up to 100lm/W
CRI	3000K
CCT	>92
SDCM	<3
UGR	<19
ELECTRICAL	
Voltage	220-240V
Power	10W
Driver (Flicker-Free)	Phase cut

5 YEARS



PURATI PTY LTD Unit 10, 80 O'Riordan St, Alexandria NSW 2015 Tel: +61 2 8065 8181 sales@purati.com

Glass diffuser or honeycomb louver

BEAM 15°/24° / 36° / 60° CRI>92 SDCM<3

Fuoco Suqare Trimless Fixed

PURATI

FSTS - W10315D FSTS - W10324D FSTS - W10336D FSTS - W10360D

DESCRIPTION

Thin trim IP54 recessed downlight with minimalistic design and versatile application


The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements.



QUICKINFO

GENERAL

Finish Materiall IP Lifespan Warranty	White(RAL9005) Die-cast Aluminium 54 L90/50,000h 5 years
LED	
Optic Lumen Efficacy CRI CCT SDCM UGR	15°/24°/36°/60° Reflector 1029Im Up to 100Im/W 3000K >92 <3 <19
ELECTRICAL	
Voltage Power Driver (Flicker-Free)	220-240V 10W Phase cut



ACCESSORIES

Glass diffuser or honeycomb louver

