







### **INTRODUCTION**

Uni-Track is a 240V 3-circuits lighting track system. It can be surface mounted, suspended, and recessed into the ceiling for residential and commercial lighting spaces. The Uni-track provides 2 colors (white and Black) and 3 sizes (1000mm, 2000mm, and 3000mm).









Surface Mounted Track

4 Wire surface mounted track

Recessed Track

4 Wire recessed track

### Uni-Track, 3 Circuits

### **QUICKINFO**

Track type 3 Circuits
Material Powder coated Aluminium
Color White, Black
Mounting Surface mounted, recessed and suspended
Length 1000mm, 2000mm and 3000mm
IP Rating 20
Warranty 5 Years

Product Code	Name	Surface Mounted Accessories	Product Code	e Name	Recessed Accessories
3C-LEC-L	Live End Connector (L	_eft)	3C-LECC-L	Live End Connector Cover (Left	27
3C-EC	End Cap	·  =	3C-REC	Recessed End Cap	N N N
3C-MJ	Mini Joiner	2   1	3C-SCC	Straight Connector Cover	n
3C-SC	Straight Connecto	or x	3C-LCC-L	L-Connector Cover (Left)	70
3C-LC-L	L-Connector (Left	B 2 0 000	3C-TCC-L	T-Connector Cover (Left)	n = = = = = = = = = = = = = = = = = = =
3C-TC-L	T-Connector (Left		3C-CCC	Crose Connector Cover	9
3C-CC	Cross Connector				
3C-FC	Flexible Connecto	or ·			

#### Suspension Accesseories

3m Wire Suspension Kit





1m Rod Supension Kit



# The elegant and precise track luminaire combination

See the table below to find out our complete contemporary track luminaires collection, selecting a pair of combinations to create your ideal lighting project.







Model

Fusi 46 Spot Uno

Fusi 46 Spot Duo

Widdei	1 usi 40 Spot Ollo	1 dsi 40 Spot Ddo			
Mounting	Track	k Light			
Materials	Powder Coated Aluminium				
Finishes	White, Black				
Track Compatibility	3 Circuit				
Adjustability	355° Rotation, 90° Tilt	355°Rotation, 180° Tilt			
Power	11W/8W	20W/15W			
Luminous Flux of Luminaire	780lm/620lm	1500lm/1200lm			
Beam Angle	15°/24°/36°/50°				
ССТ	3000K/4000K, 2700K on request				
Colour Rendering	CRI>95				
Colour Deviation	SDCM<3				
Unified Glare Rating	UGR<13				
IP Rating	IP20				
IK Rating	IK10				
Driver	Triac DIM (Dimming range: 1%-100%), non-Dim, DALI 2.0				
Lifetime	L80 50,000h				
Warranty	5 Years				
Accessories	Honeycomb Louver, Cross Louver				

### **PURATI**

## The elegant and precise track luminaire combination

See the table below to find out our complete contemporary track luminaires collection, selecting a pair of combinations to create your ideal lighting project.

	Ф 220	Ф 300	Φ 270 H52
Model	Disc 220 Track Light	Disc 300 Track Light	Pura Trim 270 Track light
Mounting	Track mounted	Track mounted	Track mounted
Materials	Aluminium + Polycarbonat	Aluminium + Polycarbonat	Polycarbonate
Finishes	White, Black, Silver on request	White, Black, Silver on request	White, Black
Adjustability	350° Rotation, 90° Tilt	350° Rotation, 90° Tilt	350° Rotation, 90° Tilt
Power	24W/18W Switch	24W/18W Switch	24W/18W/10W Switch
Luminous Flux of Luminaire	2400lm/1800lm	2400lm/1800lm	2400lm/1800lm/1000lm
Beam Angle	120°	120°	120°
ССТ	3000K/4000K Switch	3000K/4000K Switch	3000K/4000K Switch
Colour Rendering	CRI>90	CRI>90	CRI>90
Colour Deviation	SDCM<5	SDCM<5	SDCM<3
Unified Glare Rating	UGR<22 (X=4H, Y=8H)	UGR<22 (X=4H, Y=8H)	UGR<23 (X=4H, Y=8H)
IP Rating	IP20	IP20	IP20
IK Rating	IK10	IK10	IK10
Driver	Triac DIM (Dimming range: 1%-100%), non-DIM, DALI 2.0	Triac DIM (Dimming range: 1%-100%), non-DIM, DALI 2.0	Triac DIM (Dimming range: 1%-100%) non-DIM, DALI 2.0
Lifetime	L80 50,000h	L80 50,000h	L80 50,000h
Warranty	5 Years	5 Years	5 years
Accessories	3 Circuit track adapter	3 Circuit track adapter	3 Circuit track adapter

### **PURATI**

### PREMIUM ARCHITECTURAL LIGHTING