

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | Black |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|--------------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Built-in) | DALI dimming |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | Black |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|-----------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Build-in) | Phase Cut |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | Black |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|----------------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Built-in) | 1-10 V dimming |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|-----------------|-------------|
| Finish | Sliver |
| Fixture Materia | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|--------------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Build-in) | DALI dimming |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | Sliver |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|-----------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Build-in) | Phase Cut |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|-----------------|-------------|
| Finish | Sliver |
| Fixture Materia | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|----------------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Build-in) | 1-10 V dimming |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | White |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|--------------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Built-in) | DALI dimming |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | White |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|-----------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Build-in) | Phase Cut |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com

DESCRIPTION

METRICO

Perfectly integrated into contemporary architecture

Offering a classic and sleek design of Metrico linear light providing outstanding efficiency and visual comfort for both residential and commercial applications. It's indirect/direct (Up/Down) lighting. Suitable for installations requiring UGR<19 for the office environment. The linkable design solution can be configured and customised to suit any space with a wide range of accessories. Delivering high efficiency 130lm/W with flicker free driver. Available in 1.2m and 1.5 lengths.



QUICKINFO

GENERAL

| | |
|------------------|-------------|
| Finish | White |
| Fixture Material | 6063AL |
| IP | IP20 |
| Lifespan | L80/50,000h |
| Warranty | 5 years |

LED

| | |
|------------|-----------------------|
| Lumen | 4800lm↓ |
| CRI | >80 |
| CCT | 3000k / 4000k / 6000k |
| SDCM | < 3 |
| UGR | >19 |
| Beam Angle | 90° |

ELECTRICAL

| | |
|------------------|----------------|
| Voltage | 200-240V |
| Power | 40W↓ |
| Driver(Build-in) | 1-10 V dimming |

Energy efficiency class class <C>



| | | | | | |
|--------------|--------------|--------|--------|------|---------|
| Power Switch | Color Switch | CRI>80 | SDCM<3 | IP20 | 5 YEARS |
|--------------|--------------|--------|--------|------|---------|

PURATI PTY LTD

Unit 10, 80 O'Riordan St, Alexandria NSW 2015
Tel: +61 2 8065 8181
sales@purati.com