# Fuoco Move Out CNC

FMO-BV10336D

### **DESCRIPTION**

#### **Fuoco Move Out**

Part of the Fuoco Collection

The Fuoco Move Out Downlight offers both accent and general lighting with 355° rotation and 45° tilt. Designed to provide a high level of visual comfort with an outstanding colour performance CRI>97, they can be used for home and presentations, in retail situation, or in museum.



## **QUICKINFO**

#### GENERAL

Finish	Brushed Varnish
Materiall	Aluminium
IP	IP54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Lumen	600lm
Efficary	100lm/W
CRI	97
CCT	3000K/4000K/2700K on request
SDCM	<3
UGR	<19




 Voltage
 220-240V

 Power
 10W

 Driver(Build-in)
 Dimmable / DALI

 Energy efficiency class
 class <C>





→ Ø75mm 🎶 (5-25mm

PURATI PTY LTD




# **Fuoco Move Out CNC**

FMO-LB10336D

### **DESCRIPTION**

#### **Fuoco Move Out**

The Fuoco Move Out Downlight offers both accent and general lighting with 355° rotation and 45° tilt. Designed to provide a high level of visual comfort with an outstanding colour performance CRI>97, they can be used for home and presentations, in retail situation, or in museum.



## **QUICKINFO**

#### GENERAL

Finish	Light Bronze
Materiall	Aluminium
IP	IP54
Lifespan	L90/50,000h
Warranty	5 years
LED	


Lumen	600lm
Efficary	100lm/W
CRI	97
CCT	3000K/4000K/2700K on request
SDCM	<3
LICP	~10

## ELECTRICAL

220-240V Voltage Power 10W Driver(Build-in) Dimmable / DALI

Energy efficiency class class <C>





→ Ø75mm 🎶 (5-25mm

# Fuoco Move Out CNC

FMO-DB10336D

### **DESCRIPTION**

#### **Fuoco Move Out**

Part of the Fuoco Collection

The Fuoco Move Out Downlight offers both accent and general lighting with 355° rotation and 45° tilt. Designed to provide a high level of visual comfort with an outstanding colour performance CRI>97, they can be used for home and presentations, in retail situation, or in museum.



## **QUICKINFO**

## GENERAL

Finish	Dark Bronze
Materiall	Aluminium
IP	IP54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Lumen	600lm
Efficary	100lm/W
CRI	97
CCT	3000K/4000K/2700K on request
SDCM	<3



UGR

 Voltage
 220-240V


 Power
 10W

 Driver(Build-in)
 Dimmable / DALI

<19

Energy efficiency class <C>





⊙ Ø75mm ∠∠∠ 5-25mm