

PURATI

Product Coded FRTA - B10315D FRTA - B10324D FRTA - B10336D FRTA - B10360D

DESCRIPTION

Thin trim IP54 recessed downlight with minimalistic design and versatile application

The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements. Rotating design allows 350 degrees rotatable and 25 degrees tiltable.




QUICKINFO

GENERAL

Finish Materiall IP	Black (RAL 9005) Die-cast Aluminium 54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Optic	15°/ 24° / 36° / 60°
Lumen	809lm
Efficacy	100lm/W
CRI	97
CCT	3000K/4000K/2700K on request
SDCM	<3
UGR	<19
ELECTRICAL	
Voltage	220-240V
Power	10W
Driver (Flicker-Free)	Phase cut
ACCESSORIES	

IK10



PURATI PTY LTD Unit 10, 80 O'Riordan St, Alexandria NSW 2015 Tel: +61 2 8065 8181 sales@purati.com

Glass diffuser or honeycomb louver

BEAM 15°/24°/36°/60° CRI>907 SDCM<3



PURATI

Product Coded

FRTA - W10315D FRTA - W10324D FRTA - W10336D FRTA - W10360D

DESCRIPTION

Thin trim IP54 recessed downlight with minimalistic design and versatile application


The Fuoco Series comprises of two classic shapes (Round · Square) with multiple mounting options that are suitable for both consumer and professional applications. With ultra-thin trim, deep recessed design and quality light output this downlight brings a modern, eye-pleasing and elegant look to the space. Precisely designed and engineered turning lock system makes this downlight interchangeable low glare reflector with three different beam angles to meet your project requirements. Rotating design allows 350 degrees rotatable and 25 degrees tiltable.



QUICKINFO

GENERAL

Finish	White (RAL 9016)
Materiall	Die-cast Aluminium
IP.	54
Lifespan	L90/50,000h
Warranty	5 years
LED	
Optic	15°/24°/36°/60°
Lumen	809lm
Efficacy	100lm/W
CRI	97
CCT	3000K/4000K/2700K on request
SDCM	<3
UGR	<19
ELECTRICAL	
Voltage	220-240V
Power	10W
Driver (Flicker-Free)	Phase cut



ACCESSORIES

Glass diffuser or honeycomb louver

