

Ring Pro Surface 1200

Indirect, Black, 3000K, 75W, DALI

<https://purati.com/product/ring-pro-surface-1200-indirect/>

DESCRIPTION

The stylish circular luminaire for elegant and sophisticated architectural lighting design. With various finishes, 3 sizes and 2 mounting options, the Ring luminaire can be used in a variety of environments.

QUICKINFO

GENERAL

| | |
|-----------|-----------------------|
| Finish | Black |
| Material | Aluminium, Opal cover |
| IP Rating | 20 |
| IK Rating | 06 |
| Lifespan | >50,000h L80 |
| Warranty | 5 years |

LED

| | |
|-------------|-----------------------------------|
| Lumen | 9000lm |
| CCT | 3000K |
| CRI | >80 as standard, >90 on request |
| SDCM | <3 |
| Beam Angles | 120°down/120°up for Opal diffuser |

ELECTRICAL

| | |
|-------------------|----------|
| Voltage | 220-240V |
| Power | 75W |
| Driver (Built-in) | DALI |

| | | | | | |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------|------|---------|---------|
|  |  | IP20 | IK06 | CRI >80 | 5 years |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------|------|---------|---------|

